

EMS-N 408

Pompa Teknik Özellikleri / Pump Technical Specifications



Dalgıç Motor ve Pompa / Submersible Motor and Pump

PERFORMANS TABLOSU / PERFORMANCE CHART

Pompa Tipi / Pump Type	Güç / Power	Güç / Power	m ³ /h	0	2,4	3,6	4,8	6	7	9	12	13	Outlet (Inch)	Pump Dia.	Max. Pump Dia.	Pompa Uzunluğu / Pump Length	Pompa Ağırlığı / Pump Weight
	HP	kW		0	0,67	10	1,33	1,67	1,94	2,5	3,33	3,60		mm		mm	LA (mm)
408-06	1,5	1,1	MMS (m)	41	39	38	36	35	32	27	13	10	2"	94	98	4,3	4,7
408-08	2	1,5		55	52	51	48	47	43	36	17	13				627	4,9
408-13	3	2,2		89	84	83	78	76	70	58	28	21				893	6,1
408-17	4	3		116	110	108	102	99	91	76	36	27				1080	7,4
408-19	4	3		129	122	120	114	110	101	84	39	30				1185	8,1
408-22	5,5	4		150	142	139	132	128	117	98	46	35				1347	9
408-23	5,5	4		156	147	144	138	133	122	102	48	36				1400	9,4
408-30	7,5	5,5		204	193	189	180	174	160	134	63	48				1721	11,1
408-32	7,5	5,5		217	205	201	192	180	168	142	67	51				1825	11,8
408-39	10	7,5		265	251	246	234	208	197	175	82	63				2173	14

ÜRÜN ÖZELLİKLERİ

Pompa Gövdesi	Paslanmaz Çelik	AISI 304
Pompa Mili	Paslanmaz Çelik	AISI 420
Difüzör	Plastik	Norly (PPO)
Difüzör Çanağı	Paslanmaz Çelik	AISI 304
Fan	Plastik	Norly (PPO)
Kaplin	Paslanmaz Çelik	AISI 304
Filtre & Kablo Kanalı	Paslanmaz Çelik	AISI 304
Yatak Takımı	Kauçuk	NBR
Çanak Yatağı	Plastik	Poliüretan
Klepe	Paslanmaz Çelik	AISI 304
Emiş Gövdesi	Paslanmaz Çelik	AISI 304
Çıkış Gövdesi	Paslanmaz Çelik	AISI 304

PRODUCT SPECIFICATIONS

Pump Body	Stainless Steel	AISI 304
Pump Shaft	Stainless Steel	AISI 420
Diffuser	Plastic	Norly (PPO)
Diffuser Ring	Stainless Steel	AISI 304
Impeller	Plastic	Norly (PPO)
Coupling	Stainless Steel	AISI 304
Filter & Cable Guard	Stainless Steel	AISI 304
Bearing Set	Rubber	NBR
Diffuser Bearing	Plastic	Poliüretan
Valve Cap	Stainless Steel	AISI 304
Suction Body	Stainless Steel	AISI 304
Delivery Body	Stainless Steel	AISI 304