

EMS-N 406

Pompa Teknik Özellikleri / Pump Technical Specifications



Dalgıç Motor ve Pompa / Submersible Motor and Pump

PERFORMANS TABLOSU / PERFORMANCE CHART

Pompa Tipi / Pump Type	Güç / Power	Güç / Power	m ³ /h	0	2	3,6	5,2	6,2	7,2	8,5	Outlet (Inch)	Pump Dia.	Max. Pump Dia.	Pompa Uzunluğu / Pump Length	Pompa Ağırlığı / Pump Weight
	HP	kW		0	0,55	10	1,44	1,72	20	2,36		mm	mm	LA (mm)	Kg
406-07	1	0,75	MMS (m)	49	46	42	39	29	22	13	2"	94	98	425	4,7
406-09	1,5	1,1		64	60	54	51	38	29	17				618	9,2
406-10	1,5	1,1		71	65	60	55	41	31	18				654	9,4
406-11	2	1,5		78	72	66	60	46	34	20				690	9,7
406-14	2	1,5		99	90	84	75	58	42	24				798	10,4
406-17	3	2,2		120	110	102	92	71	52	30				911	11
406-20	3	2,2		140	129	120	108	83	60	35				1019	11,7
406-23	4	3		162	149	138	125	96	70	41				1136	12,3
406-27	4	3		190	174	162	145	113	82	48				1280	13,2
406-32	5,5	4		226	207	192	173	134	98	57				1500	14,3
406-36	5,5	4		254	232	216	195	150	110	63				1640	15,3
406-45	7,5	5,5		318	291	270	244	188	138	80				1910	16,4
406-49	7,5	5,5		345	316	294	265	204	149	87				2208	17,4

ÜRÜN ÖZELLİKLERİ

Pompa Gövdesi	Paslanmaz Çelik	AISI 304
Pompa Mili	Paslanmaz Çelik	AISI 420
Difüzör	Plastik	Norly (PPO)
Difüzör Çanağı	Paslanmaz Çelik	AISI 304
Fan	Plastik	Norly (PPO)
Kaplin	Paslanmaz Çelik	AISI 304
Filtre & Kablo Kanalı	Paslanmaz Çelik	AISI 304
Yatak Takımı	Kauçuk	NBR
Çanak Yatağı	Plastik	Poliüretan
Klepe	Paslanmaz Çelik	AISI 304
Emiş Gövdesi	Paslanmaz Çelik	AISI 304
Çıkış Gövdesi	Paslanmaz Çelik	AISI 304

PRODUCT SPECIFICATIONS

Pump Body	Stainless Steel	AISI 304
Pump Shaft	Stainless Steel	AISI 420
Diffuser	Plastic	Norly (PPO)
Diffuser Ring	Stainless Steel	AISI 304
Impeller	Plastic	Norly (PPO)
Coupling	Stainless Steel	AISI 304
Filter & Cable Guard	Stainless Steel	AISI 304
Bearing Set	Rubber	NBR
Diffuser Bearing	Plastic	Poliüretan
Valve Cap	Stainless Steel	AISI 304
Suction Body	Stainless Steel	AISI 304
Delivery Body	Stainless Steel	AISI 304