

EMS-D 5025

Pompa Teknik Özellikleri / Pump Technical Specifications



Dalgıç Motor ve Pompa / Submersible Motor and Pump

PERFORMANS TABLOSU / PERFORMANCE CHART

| Pompa Tipi / Pump Type | Motor Tipi / Motor Type | Güç / Power | Güç / Power | m ³ /h | 0 | 10,8 | 14,4 | 18 | 21,6 | 25 | 28,8 | 32,4 | 36 | Outlet (Inch) | Pump Dia. | Max. Pump Dia. | Pompa Uzunluğu / Pump Length | Pompa Ağırlığı / Pump Weight |
|------------------------|-------------------------|-------------|-------------|-------------------|------|------|------|-----|------|----|------|------|----|---------------|-----------|----------------|------------------------------|------------------------------|
| | | HP | kW | | lt/s | 0 | 3 | 4 | 5 | 6 | 7 | 8 | 9 | | 10 | mm | mm | LA (mm) |
| 5025 / 03 | 4" 5" 6" | 3 | 2,2 | MMS (m) | 27 | 25 | 23 | 22 | 20 | 19 | 18 | 16 | 15 | 2 1/2" 3" | 125 | 135 | 750 | 24 |
| 5025 / 04 | | 4 | 3 | | 36 | 32 | 30 | 28 | 27 | 26 | 24 | 22 | 20 | | | | 833 | 27 |
| 5025 / 05 | | 5,5 | 4 | | 45 | 38 | 37 | 36 | 34 | 32 | 30 | 28 | 25 | | | | 916 | 30 |
| 5025 / 09 | | 7,5 | 5,5 | | 72 | 62 | 60 | 57 | 54 | 52 | 47 | 43 | 40 | | | | 1082 | 36 |
| 5025 / 10 | | 10 | 7,5 | | 85 | 77 | 73 | 71 | 68 | 64 | 60 | 55 | 52 | | | | 1248 | 42 |
| 5025 / 12 | | 12,5 | 9,2 | | 100 | 92 | 88 | 85 | 80 | 78 | 72 | 67 | 62 | | | | 1497 | 51 |
| 5025 / 15 | | 15 | 11 | | 125 | 115 | 110 | 105 | 100 | 92 | 87 | 78 | 70 | | | | 1663 | 57 |

ÜRÜN ÖZELLİKLERİ

| | | |
|----------------------------|-----------------|----------|
| Difüzör | Pik Döküm | GG20 |
| Fan ** | Pik Döküm | GG20 |
| Çıkış Gövdesi | Pik Döküm | GG20 |
| Emme Kutusu | Pik Döküm | GG20 |
| Pompa Mili | Paslanmaz Çelik | AISI 420 |
| Kaplin | Paslanmaz Çelik | AISI 420 |
| Filtre & Kablo Kanalı | Paslanmaz Çelik | AISI 304 |
| Klepe | Paslanmaz Çelik | AISI 304 |
| ** Bronz Fan Opsiyoneldir. | | |

PRODUCT SPECIFICATIONS

| | | |
|---------------------------------|-----------------|----------|
| Diffuser | Cast Iron | GG20 |
| Impeller ** | Cast Iron | GG20 |
| Outlet Body | Cast Iron | GG20 |
| Suction Case | Cast Iron | GG20 |
| Pump Shaft | Stainless Steel | AISI 420 |
| Coupling | Stainless Steel | AISI 420 |
| Filter & Cable Guard | Stainless Steel | AISI 304 |
| Valve Cap | Stainless Steel | AISI 304 |
| ** Bronze Impeller is Optional. | | |